Knockout punch set 16-63

Knockout punches, round M16 - M63



Self-centering knockout punches for stainless steel or mild steel, aluminium and plastic walls with max. sheet thickness of 3 mm. Punches for cut-outs M16, M20, M25, M32, M40, M50 and M63. Cut-outs for icotek split cable glands and round cable entry plates can be punched.

The special cutting geometry of the punch reduces the cutting pressure and therefore the required effort. The punch splits slugs into several pieces (type related) for easy slug removal.

The punches are designed for manual and hydraulic operation.

Scope of delivery:

• 1 each knockout punch M16 | M20 | M25 | M32 | M40 | M50 | M63

Specifications

Material

Steel, hardened and burnished

Advantages & Benefits

Multiple splitting punches for easier slug removal/ for easy punching

Suitable for hand hydraulic punch driver by icotek and other manufacturers

Product Types & Sizes

Punch V2A set M16 - M63



No. 42512 EAN 69323 935 Packag 1 quanti ty Punchi Mild ng steel materi (St), Stainl ess steel (V2A) Suitabl 80201 e draw/ stud **80210**

Part

80070

Punch set M16 - M63



Part **80007** No. EAN **42512** 69316 579 Packag **1** e quanti ty Punchi **Mild** ng steel materi (St) al Suitabl **80200** e draw/ stud **80201**

